





Classy pattern inspired by fine sparkles on the water surface. Sheer persistence to yarn texture and chromogenic effect will provide a premium feel.

Composition	surface	BCF Nylon 100%		dyeing method of yarn		Piece Dyed		
	base fabric	Nonwoven Polyester		, ,	, , ,			
			,	-	backing		PVC and Glass Fiber	
Specification	size	250m	m×1000mm	overall thick	ness	8.0mm		
	pile height	H 5.0n	mm / M 4.5mm / L 3.5mm (textured loop pile: tip sheared)					
	gauge 1/10		stitch	11.5	yarn weig	ht (oz/sq.yd)	20.6	
Packing	12pcs/box = 3m ² /box							
Net Weight	17.0kg/box							
Performance	Critical Radiant Flux	(A	STM E648) 0	Image CRF 0.45/cm² or higher				
	Smoke Density	(A	STM E662)	Less than 450				
	Flame-retardant	t Fire Defense Law in Japan Authorized No.E2180256						
	Antistatic	Less than 1.0kv (JIS L 1021-16, at 23 degrees centigrade, 25%RH)						
	Stain-resistant	Stain Release						
	Formaldehyde Radiation	F "太太太太 Interior-fabrics Performance Evaluation Conference Certified No. J18-21148					8-21148	
Way of Installation	Î <mark>↑</mark> Î Ashlar or Î↑Î↑Î Monolithic							
Recommended Adhesive from TOLI		,		for steel or plastic	sub-floor	40 to 60 g	ram/m²	
	TOLI ECO GA Cement	(required quantity) -	for mortar and woo	d sub-floor	60 to 100 g	(ram/m²	
Notes on Installation	 Apply the adhesive on the whole surface of the sub-floor thinly and evenly. After drying, when the adhesive becomes translucent, install the tiles. Be careful not to put the tiles too tightly. When you install DIFFEBRILLER on the free access floor, each tile should be laid to stride over the joint of free access floor panels in the middle. (The joint of DIFFEBRILLER should not be matched to that of free access floor panels.) Occasionally the direction of tip sheared piles are partly broken in part, which looks like color shading. This is one of the characteristics of tip sheared carpets and not a manufacturing defect. 							
Others	 The color shading differs on a tile-by-tile basis. In case you do not feel comfortable about the floor after installation, please change the tiles partly so that it will look natural. Please note that the product has the indigenous odor from its materials. 							

MADE IN JAPAN





GX9651V



GX9652V



GX9653V

116







GX9655V







▲ GX9651V/GX9655V/TTN3112/TTN3113 (LL FREE 50 NW-EX · page 322)

