



LONG LIFE CA-100S category: carpet tile

GA-100's sister product which has a beautiful stripe

image.
GOOD DESIGN LONG LIFE DESIGN AWARD-winning product in 2015.

Composition	surface	BCF Nylon 100%		dyeing method o	f yarn Piece Dy	Piece Dyed	
	base fabric	Nonwoven Polyester		backing	PVC and Gla	PVC and Glass Fiber	
Specification	size	500mm x 500mm		overall thickne	ess 6.5mr	6.5mm	
	pile height	H 3.5mm / L 3.0mm (high and low loop pile)					
	gauge	1/10	stitch	13.0	yarn weight (oz/sq.yd)	17.7	
JIS Registered No.	No. QT0508001 QT0408001 (JIS L 4406 Carpet Tile)						

Packing	$20pcs/box = 5m^2/box$						
Net Weight	24.0kg/box						
Performance	Critical Radiant Flux	(ASTM E648) Class 1 Average CRF 0.45/cm ² or higher		gher			
	Smoke Density (flaming)	(ASTM E662)	Less than 450				
	Flame-retardant	Fire Defense Law in Japan Authorized No.E0080216					
	Antistatic	Less than 1.0kv (JIS L 1021-16, at 23 degrees centigrade, 25%RH)					
	Stain-resistant	Stain Release					
	Formaldehyde Radiation	F [™] ☆☆☆☆ Interior-fabrics Performance Evaluation Conference Certified No. J06-30344					
Way of Installation	Quarter Turn						
Recommended Adhesive from TOLI	TOLL 500 CA Compant	(for steel or plastic sub-floor	40 to 60 gram/m ²			
	TOLI ECO GA Cement	(required quantity)	for mortar and wood sub-floor	60 to 100 gram/m ²			
Notes on Installation	 ◆Apply the adhesive on the whole surface of the sub-floor thinly and evenly. After drying, when the adhesive becomes translucent, install the tiles. Be careful not to put the tiles too tightly. ◆Due to striped designs, the crossover point of joints may appear to be misaligned. This is optional illusion, not a mamufacturing defect. 						
Others	Please note that the product has the indigenous odor from its materials.						

MADE IN JAPAN














|| GA1202S




GA1207S

GA1206S









 $\blacktriangle \ \ \mathsf{GA1207S}/\mathsf{GA1021} \ (\mathsf{GA-100} \cdot \mathsf{page} \ \mathsf{22})$

GA1208S