



LONG LIFE DESIGN



GA-100W (standard)

category: carpet tile

GA-100W (standard) is characterized by its delicate stripe design. Beautiful colored piles will create a new standard of monolithic installation.
GOOD DESIGN LONG LIFE DESIGN AWARD-winning product in 2015.

Carpet

Composition	surface	BCF Nylon 100%	dyeing method of yarn	Piece Dyed	
	base fabric	Nonwoven Polyester	backing	PVC and Glass Fiber	
Specification	size	500mm x 500mm	overall thickness	6.5mm	
	pile height	H 3.5mm / L 2.5mm (high and low loop pile)			
	gauge	1/10	stitch	14.0	yarn weight (oz/sq.yd)
Packing	20pcs/box = 5m ² /box				
Net Weight	24.0kg/box				
Performance	Critical Radiant Flux	(ASTM E648)	Class 2 Average CRF 0.22/cm ² or higher		
	Smoke Density (flaming)	(ASTM E662)	Less than 450		
	Flame-retardant	Fire Defense Law in Japan Authorized No.E0100047			
	Antistatic	Less than 1.0kv (JIS L 1021-16, at 23 degrees centigrade, 25%RH)			
	Stain-resistant	Stain Release			
	Formaldehyde Radiation	F☆☆☆☆ Interior-fabrics Performance Evaluation Conference Certified No. J10-30669			
Way of Installation	Monolithic or Quarter Turn				
Recommended Adhesive from TOLI	TOLI ECO GA Cement	(required quantity)	for steel or plastic sub-floor	40 to 60 gram/m ²	
			for mortar and wood sub-floor	60 to 100 gram/m ²	
Notes on Installation	Apply the adhesive on the whole surface of the sub-floor thinly and evenly. After drying, when the adhesive becomes translucent, install the tiles. Be careful not to put the tiles too tightly.				
Others	♦The stripes differ in position on a tile-by-tile basis so that they will not be exactly connected between the tiles (please refer to the installation image). ♦Please note that the product has the indigenous odor from its materials.				

MADE IN JAPAN



GA1301W



GA1301W



GA1304W



▲ GA1304W



GA1302W



GA1305W



GA1303W