

GA-3600 (texture I)

Natural design and texture inspired by the bark of trees are well described in beautiful earth color tones.

category: carpet tile

Composition	surface	BCF I	lylon 100%		dyeing method of yarn		Solution Dyed		
	base fabric	Nonwo	en Polyester		backing		PVC and Glass Fiber		
Specification	size	500m	m x 500mm		overall thickness		6.8mm		
	pile height	H 4.5mm / L 3.0mm (textu			ed loop pile)				
	gauge 1/10		stitch		12.5	12.5 yarn weig		16.5	
Packing	$16 \text{pcs/box} = 4 \text{m}^2/\text{box}$								
Net Weight	19.2kg/box								
Performance	Critical Radiant Flux	(AS			2 Average CRF 0.22/cm ² or higher				
	Smoke Density	(A9	STM E662)		Less than 450				
	Flame-retardant	Fire Defense			e Law in Japan Authorized No.E2120246				
	Antistatic		Less than 1.0kv (JIS L 1021-16, at 23 deg				rees centigrade, 25%RH)		
	Stain-resistant	Stain Release							
	Formaldehyde Radiation	F™☆☆	☆☆ Interior-fabr	abrics Performance Evaluation Conference Certified No.J12-30849					
Way of Installation	$\uparrow \uparrow \uparrow$ $\uparrow f \uparrow f$ $\downarrow f \uparrow f$ $\downarrow f \uparrow f$ $\downarrow f \uparrow f$ $\downarrow f \downarrow f$								
Recommended Adhesive from TOLI	TOLI ECO GA Cement	(for steel or plastic su	ub-floor	40 to 60 gr	am/m²	
	TOLI ECO GA Cement	(required quantity) –		1	for mortar and wood s	sub-floor	60 to 100 g	ram/m²	
Notes on Installation	Apply the adhesive on the whole surface of the sub-floor thinly and evenly. After drying, when the adhesive becomes translu- cent, install the tiles. Be careful not to put the tiles too tightly.								
Others	 To have a natural image after installation, stripes are intentionally inserted in the design at regular intervals, which is not a manufacturing defect. In case you do not feel comfortable about the floor after installation, please change the tiles partly so that it will look natural. Please note that the product has the indigenous odor from its materials. 								

MADE IN JAPAN



made-to-order product



Any color from GA-3600 can be "Eco-Friendly" for more than $1,000m^2$ of order per color.

GA-3600EM



GA-3600 with approx. 23% post-consumer & 6% post-indutrial recycled backing



GA3601



GA3607



GA3603



GA3608



GA3605



GA3609





GA3611





Carpet





GA3613

GA3614



▲ GA3605/GA3611