





OCASH <GX-2400>

category: carpet tile

OCASH is an innovative carpet tile product using silver yarn. Once it's installed, a subtle random design will be spread on the floor, which can create cool atmosphere.

Composition	surface	BCF Nylon 100%		dyeing method of yarn	Solution Dyed
	base fabric	Nonwoven Polyester		backing	PVC and Glass Fiber
Specification	size	500mm x 500mm		overall thickness	7.0mm
	pile height	H 4.0mm / L 3.0mm (textured loop pile)			
	gauge	1/8	stitch	11.5	yarn weight (oz/sq.yd)
Packing	16pcs/box = 4m ² /box				
Net Weight	20.7kg/box				
Performance	Critical Radiant Flux	(ASTM E648)	Class 1 Average CRF 0.45/cm ² or higher		
	Smoke Density	(ASTM E662)	Less than 450		
	Flame-retardant	Fire Defense Law in Japan Authorized No.E0080040			
	Antistatic	Less than 1.0kv (JIS L 1021-16, at 23 degrees centigrade, 25%RH)			
	Stain-resistant	Stain Release			
	Formaldehyde Radiation	F☆☆☆☆ Interior-fabrics Performance Evaluation Conference Certified No. J08-30517			
Way of Installation	 Monolithic or  Quarter Turn				
Recommended Adhesive from TOLI	TOLI ECO GA Cement	(required quantity)	for steel or plastic sub-floor	40 to 60 gram/m ²	
			for mortar and wood sub-floor	60 to 100 gram/m ²	
Notes on Installation	Apply the adhesive on the whole surface of the sub-floor thinly and evenly. After drying, when the adhesive becomes translucent, install the tiles. Be careful not to put the tiles too tightly.				
Others	◆To have a natural image after installation, stripes are intentionally inserted in the design at regular intervals, which is not a manufacturing defect. In case you do not feel comfortable about the floor after installation, please change the tiles partly so that it will look natural. ◆Please note that the product has the indigenous odor from its materials.				

MADE IN JAPAN



GX2402




|| GX2402



|| GX2404



|| GX2403



|| GX2401



▲ GX2404