





ORVIE <GX-8300>

category: carpet tile

Beautiful random block pattern created by multi-colored cut & loop piles — ORVIE's 3-dimensional image will be more clearly shown by light reflection.

Carpet

Composition	surface	BCF Nylon 100%	dyeing method of yarn	Solution Dyed	
	base fabric	Nonwoven Polyester	backing	PVC and Glass Fiber	
Specification	size	500mm x 500mm	overall thickness	9.0mm	
	pile height	H 6.5mm / L 4.5mm (cut and loop pile)			
	gauge	1/10	stitch	12.0	yarn weight (oz/sq.yd)
Packing	16pcs/box = 4m ² /box				
Net Weight	19.2kg/box				
Performance	Critical Radiant Flux	(ASTM E648)	Class 1. Average CRF 0.45/cm ² or higher		
	Smoke Density	(ASTM E662)	Less than 450		
	Flame-retardant	Fire Defense Law in Japan Authorized No.E2150031			
	Antistatic	Less than 1.0kv (JIS L 1021-16, at 23 degrees centigrade, 25%RH)			
	Stain-resistant	Stain Release			
Formaldehyde Radiation	F ¹ ☆☆☆☆ Interior-fabrics Performance Evaluation Conference Certified No. J15-31027				
Way of Installation	 Monolithic or  Quarter Turn				
Recommended Adhesive from TOLI	TOLI ECO GA Cement	(required quantity)	for steel or plastic sub-floor	40 to 60 gram/m ²	
			for mortar and wood sub-floor	60 to 100 gram/m ²	
Notes on Installation	Apply the adhesive on the whole surface of the sub-floor thinly and evenly. After drying, when the adhesive becomes translucent, install the tiles. Be careful not to put the tiles too tightly.				
Others	♦Occasionally the direction of cut-piles are partly broken in part, which looks like color shading. This is one of the characteristics of cut-pile carpets and not a manufacturing defect. ♦Please note that the product has the indigenous odor from its materials.				

MADE IN JAPAN



GX8301



|| GX8301



|| GX8302



▲ GX8301