



Multi-colored rustic feeling of painted woods is very well expressed in VENICHE.

category: carpet tile

Composition	surface	BCF I	Nylon 100% dyeing method of yarn		of yarn Solution D	Solution Dyed	
	base fabric	Nonwo	ven Polyester	backing	PVC and Glass	PVC and Glass Fiber	
Specification	size	250mm x 1000mm		overall thickn	ess 8.3mm	8.3mm	
	pile height	H 5.5mm / M 4.0mm / L 3.0mm (textured loop pile)					
	gauge	1/10	stitch	11.0	yarn weight (oz/sq.yd)	20.1	

		<u> </u>	•				
Packing	12pcs/box = 3m ² /box						
Net Weight	16.0kg/box						
Performance	Critical Radiant Flux (ASTM E648) Class 1 Average CRF 0.45/cm ² or higher						
	Smoke Density	oke Density (ASTM E662) Less than 450					
	Flame-retardant	Fire Defense Law in Japan Authorized No.E2150035					
	Antistatic	Less than 1.0kv (JIS L 1021-16, at 23 degrees centigrade, 25%RH)					
	Stain-resistant	Stain Release					
	Formaldehyde Radiation	F ☆☆☆☆ Interior-fabrio	abrics Performance Evaluation Conference Certified No. J15-31031				
Way of Installation	↑ ↑ ↑ Ashlar or ↑↑↑↑ Monolithic						
Recommended Adhesive from TOLI	TOLL FOO CA Compant	(un accional accountita)	for steel or plastic sub-floor	40 to 60 gram/m ²			
	TOLI ECO GA Cement	(required quantity) -	for mortar and wood sub-floor	60 to 100 gram/m ²			
Notes on Installation	◆Apply the adhesive on the whole surface of the sub-floor thinly and evenly. After drying, when the adhesive becomes translucent, install the tiles. Be careful not to put the tiles too tightly. ◆When you install VENICHE on the free access floor, each tile should be laid to stride over the joint of free access floor panels in the middle. (The joint of VENICHE should not be matched to that of free access floor panels.)						
Others	◆The color shading differs on a tile-by-tile basis. In case you do not feel comfortable about the floor after installation, please change the tiles partly so that it will look natural. ◆Please note that the product has the indigenous odor from its materials.						

MADE IN JAPAN



▲ GX9151V/GX9152V





GX9151V



GX9152V



GX9153V