

CORENTE V is one of the products of "VARY collection", the new concept of carpet tiles that won GOOD DESIGN AWARD 2007. Beautiful combination of solution dyed yarn and space dyed yarn in 250mm x 1000mm plank orm can create variety of images

		-		form can create variety of images.				
Composition	surface	BCF	Nylon 100%	dyeing method of y	arn Soluti	Solution Dyed and Space Dyed		
	base fabric	Nonwoven Polyester		backing		PVC and Glass Fiber (Recycled PVC contained)		
Specification	size	250mm x 1000mm		overall thickness	;	6.5mm		
	pile height	3.5mn	n (loop pile)					
	gauge 1/10		stitch	14.5	yarn weig	ht (oz/sq.yd)	20.1	
Packing	12pcs/box = 3m <sup>2</sup> /box							
Net Weight	15.6kg/box							
Performance	Critical Radiant Flux	(A)	STM E648)	Class 2 Average CRF 0.22	2/cm² or highe	r		
	Smoke Density (flaming)	(A)	STM E662)	Less than 45	0			
	Flame-retardant	Fire Defense Law in Japan Authorized No.E0060172						
	Antistatic	Less than 1.0kv (JIS L 1021-16, at 23 degrees centigrade, 25%RH)						
	Stain-resistant	Stain Release						
	Formaldehyde Radiation	F <sup>™</sup> ☆☆☆☆ Interior-fabrics Performance Evaluation Conference Certified No. J06-30417						
Way of Installation	↑↑↑↑ Ashlar							
Recommended Adhesive from TOLI	TOLI ECO GA Cement			for steel or plastic s	ub-floor	40 to 60 gr	am/m²	
	TOLI ECO GA Cement	(required quantity) –		for mortar and wood	sub-floor	60 to 100 g	ram/m²	
Notes on Installation	<ul> <li>Apply the adhesive on the whole surface of the sub-floor thinly and evenly. After drying, when the adhesive becomes translucent, install the tiles. Be careful not to put the tiles too tightly.</li> <li>The color shading differs on a tile-by-tile basis. In case you do not feel comfortable adout the floor after installation, please change the tiles partly so that it will look natural.</li> <li>When you install CORENTE V on the free access floor, each tile should be laid to stride over the joint of free access floor panels in the middle. (The joint of CORENTE V should not be matched to that of free access floor panels.)</li> <li>Avoid the installation at temperature of 5 degrees centigrade or lower.</li> </ul>							
Others	Please note that the product has the indigenous odor from its materials.							

CORENTE V <GX-9300V>

category: carpet tile

## MADE IN JAPAN







GX9307V

GX9306V

GX9308V





## GX9301V



GX9302V









Carpet



▲ GX9302V/GX9307V



▲ GX9301V/GX9302V/GX9303V