





## category: carpet tile

With its top-selling history for more than 35 years, GA-100 is now the synonym for Japanese carpet tiles. Good quality and performance is assured in versatile application.

GOOD DESIGN LONG LIFE DESIGN AWARD-winning

product in 2015.

Composition	surface	BCF Nylon 100%		dyeing method o	of yarn Pi	Piece Dyed	
	base fabric	Nonwoven Polyester		backing	PVC ar	PVC and Glass Fiber	
	size	500mm×500mm		overall thickn	ess	6.5mm	
Specification	pile height	3.5mm (loop pile)					
	gauge	1/10	stitch	13.0	yarn weight (oz/so	q.yd)	17.7
JIS Registered No.	No. QT0508001 QT0408001 (JIS L 4406 Carpet Tile)						
Packing	$20pcs/box = 5m^2/box$						

Packing	20pcs/box = 5m <sup>2</sup> /box					
Net Weight	24.0kg/box					
Performance	Critical Radiant Flux	(ASTM E648) Class 1 Average CRF 0.45/cm² or higher				
	Smoke Density (flaming)	(ASTM E662) Less than 450				
	Flame-retardant	Fire Defense Law in Japan Authorized No.E0830367				
	Antistatic	Less than 1.0kv (JIS L 1021-16, at 23 degrees centigrade, 25%RH)				
	Stain-resistant	Stain Release / ◆ Stain Release (NANO CLEAN)				
	Formaldehyde Radiation	F <sup>™</sup> ☆☆☆☆ Interior-fabrics Performance Evaluation Conference Certified NO.J04-30066				
Way of Installation	Quarter Turn					
Recommended Adhesive from TOLI	TOLI ECO GA Cement (required quantity) for steel or plastic sub-floor 40 to 60 gram/1					
	TOLI ECO GA Cement	(required quantity) for mortar and wood sub-floor 60 to 100 gram/m²				
Custom Order	All the standard colors of GA-100 can be made with Nano Clean finish (patent-obtained special stain release) on a made-to-order basis. For more information, please contact TOLI sales reps.					
Notes on Installation	Apply the adhesive on the whole surface of the sub-floor thinly and evenly. After drying, when the adhesive becomes translucent, install the tiles. Be careful not to put the tiles too tightly.					
Others	Please note that the product has the indigenous odor from its materials.					

MADE IN JAPAN



