



LONG LIFE
DESIGN



GA-100W (RANDOM)

category: carpet tile

GA-100W (RANDOM) has a very impressive image where the stripes are melted in the base yarn with subtle color changes.
GOOD DESIGN LONG LIFE DESIGN AWARD-winning product in 2015.

Composition	surface		BCF Nylon 100%		dyeing method of yarn		Piece Dyed	
	base fabric		Nonwoven Polyester		backing		PVC and Glass Fiber	
Specification	size		500mm×500mm		overall thickness		6.5mm	
	pile height		H 4.0mm / L 3.0mm (high and low loop pile)					
	gauge		1/10	stitch		12.5	yarn weight (oz/sq.yd) 17.1	
Packing	20pcs/box = 5m ² /box							
Net Weight	25.0kg/box							
Performance	Critical Radiant Flux		(ASTM E648)		Class 2 Average CRF 0.22/cm ² or higher			
	Smoke Density		(ASTM E662)		Less than 450			
	Flame-retardant		Fire Defense Law in Japan Authorized No.E0100077					
	Antistatic		Less than 1.0kV (JIS L 1021-16, at 23 degrees centigrade, 25%RH)					
	Stain-resistant		Stain Release					
	Formaldehyde Radiation		F☆☆☆☆ Interior-fabrics Performance Evaluation Conference Certified No. J10-30670					
Way of Installation	<div><div><div><div>↑</div><div>↑</div></div><div><div>↑</div><div>↑</div></div></div>Monolithic</div> or <div><div><div>↑</div><div>→</div></div><div><div>→</div><div>↑</div></div></div> Quarter Turn							
Recommended Adhesive from TOLI	TOLI ECO GA Cement		(required quantity)		for steel or plastic sub-floor		40 to 60 gram/m ²	
					for mortar and wood sub-floor		60 to 100 gram/m ²	
Notes on Installation	Apply the adhesive on the whole surface of the sub-floor thinly and evenly. After drying, when the adhesive becomes translucent, install the tiles. Be careful not to put the tiles too tightly.							
Others	♦The stripes differ in position on a tile-by-tile basis so that they will not be exactly connected between the tiles (please refer to the installation image). ♦Please note that the product has the indigenous odor from its materials.							
Custom Order	All the standard colors of GA-100W can be made with Nano Clean finish (patent-obtained special stain release) on a made-to-order basis. For more information, please contact TOLI sales reps.							

MADE IN JAPAN




GA1413W



GA1414W



GA1412W



GA1413W



▲ GA1412W/GA1413W/GA1414W