



LUCEART <GX-8500>

category: carpet tile


LUCEART conveys the image of natural scenery sparkling with light reflection. Its color mixture and uneven texture can create a rich expression.

Composition	surface	BCF Nylon 100%	dyeing method of yarn	Solution Dyed	
	base fabric	Nonwoven Polyester	backing	PVC and Glass Fiber	
Specification	size	500mm×500mm	overall thickness	9.3mm	
	pile height	H 6.5mm / M 5.5mm/ L 3.0mm (textured loop pile)			
	gauge	1/10	stitch	16.0	yarn weight (oz/sq.yd)
Packing	16pcs/box = 4m ² /box				
Net Weight	19.6kg/box				
Performance	Critical Radiant Flux	(ASTM E648)	Class 1 Average CRF 0.45/cm ² or higher		
	Smoke Density	(ASTM E662)	Less than 450		
	Flame-retardant	Fire Defense Law in Japan Authorized No.E2150033			
	Antistatic	Less than 1.0kv (JIS L 1021-16, at 23 degrees centigrade, 25%RH)			
	Stain-resistant	Stain Release			
Formaldehyde Radiation	F☆☆☆☆ Interior-fabrics Performance Evaluation Conference Certified No. J15-31029				
Way of Installation	Monolithic		or	Quarter Turn	
Recommended Adhesive from TOLI	TOLI ECO GA Cement	(required quantity)	for steel or plastic sub-floor	40 to 60 gram/m ²	
			for mortar and wood sub-floor	60 to 100 gram/m ²	
Notes on Installation	Apply the adhesive on the whole surface of the sub-floor thinly and evenly. After drying, when the adhesive becomes translucent, install the tiles. Be careful not to put the tiles too tightly.				
Others	<ul style="list-style-type: none"> ◆The color shading differs on a tile-by-tile basis. In case you do not feel comfortable about the floor after installation, please change the tiles partly so that it will look natural. ◆Please note that the product has the indigenous odor from its materials. 				

MADE IN JAPAN



GX8502



GX8501



GX8504



▲ GX8501



GX8502



GX8505



GX8503

※In GX8502 soft stripes are described within the pattern. By changing the direction of installation, you can have different floor images.