

CO2

ROYAL STONE HIGH-END

(260mm rhombus)

ROYAL STONE in rhombus size will make very unique diamond-shaped floor designs.

category: solid vinyl tile


Specification	overall thickness	3.0mm	size	260mm rhombus
	others	Surface Clear Wear Layer 0.3mm / Beveled		

Packing	48pcs/box = 2.80m ²		
Net Weight	14 .6kg/box		
Recommended Adhesive from TOLI	dried mortar and concrete	Eco AR600	
	humid mortar and concrete	Epo Gray ST, US Cement, US Cement (less-smelly), US200	
Notes on Installation	 ◆For one week after installation, direct sunlight, sudden change of temperature due to air conditioning, and water washing should be avoided. ◆The color shading differs on a tile-by-tile basis, which will make the floor look very natural when the tiles are installed. 		
Recommended Maintenance Wax from TOLI	New FB Wax, U Wax, T Wax (Non-shiny & Antibacterial)		
Others	 ◆The dirt and stains will be more visible on the floor covering with lighter plain colors, compared to dark colors. Also they are more likely to stick with the deep-embossed surface than the flat surface. ◆Please be aware that some rubber casters might cause color-contamination. ◆Please bear in mind that ROYAL STONE (rhombus) may take more time for layout and installation compared to the tiles in square size. ◆Please note that the product has the indigenous odor from its materials. ◆When you install the tiles in rhombus size, you will have a better appearance by finishing the joints with cauking materials. ◆Occasionally a very slight size difference could be seen between different production lots. For designed installation of 4-sides-beveled tiles, or installation of tiles with the shape of triangle, hexagon, and rhombus, please adjust the size of a tile as needed. Otherwise joints should be finished with caulking compound. ◆Squareness of tiles are fully checked during the production. However, due to the condition of sub-floor and others, joints might not be strictly matched in some cases. 		











▲ PST1312/PST1313/PST1314