




GA-560

category: carpet tile

GA-560 has an urbanized block pattern made by uneven texture of loop piles. Combination with GA-400 is also recommendable.

Carpet Tile

| | | | | | |
|--------------------------------|--|--|--------------------------------|-------------------------------|------------------------|
| Composition | surface | Polypropylene 100% | dyeing method of yarn | Solution Dyed | |
| | base fabric | Nonwoven Polyester | backing | PVC and Glass Fiber | |
| Specification | size | 500mm×500mm | overall thickness | 7.0mm | |
| | pile height | H 4.5mm / L 3.0mm (textured loop pile) | | | |
| | gauge | 1/10 | stitch | 13.0 | yarn weight (oz/sq.yd) |
| Packing | 20pcs/box = 5m ² /box | | | | |
| Net Weight | 21.5kg/box | | | | |
| Performance | Smoke Density | (ASTM E662) | Less than 450 | | |
| | Flame-retardant | Fire Defense Law in Japan Authorized No.E2150022 | | | |
| | Antistatic | Less than 1.0kV (JIS L 1021-16, at 23 degrees centigrade, 25%RH) | | | |
| | Formaldehyde Radiation | F☆☆☆☆ Interior-fabrics Performance Evaluation Conference Certified No. J15-31020 | | | |
| Way of Installation |  Quarter Turn | | | | |
| Recommended Adhesive from TOLI | TOLI ECO GA Cement | (required quantity) | for steel or plastic sub-floor | 40 to 60 gram/m ² | |
| | | | for mortar and wood sub-floor | 60 to 100 gram/m ² | |
| Notes on Installation | Apply the adhesive on the whole surface of the sub-floor thinly and evenly. After drying, when the adhesive becomes translucent, install the tiles. Be careful not to put the tiles too tightly. | | | | |
| Others | Please note that the product has the indigenous odor from its materials. | | | | |

MADE IN JAPAN



GA5604

The color numbers marked ◆ can be coordinated with GA-400.

| | | |
|--------|------------------|------------------|
| GA5601 | GA4005 (page 78) | GA4035 (page 78) |
| GA5602 | GA4005 (page 78) | — |
| GA5604 | GA4003 (page 78) | GA4004 (page 78) |



GA5601



GA5602



GA5604



▲ GA5604/GA4031 (GA-400 · page 78)