





# GA-550

category: carpet tile

Beautiful deep-colored stripes are well expressed by ripple-like piles. GA-550 will give a calm and luxurious impression in your space.

Carpet Tile

Composition	surface	Polypropylene 100%	dyeing method of yarn	Solution Dyed	
	base fabric	Nonwoven Polyester	backing	PVC and Glass Fiber	
Specification	size	500mm×500mm		overall thickness	7.0mm
	pile height	H 4.5mm / L 3.0mm (multi-level loop pile)			
	gauge	1/10	stitch	13.0	yarn weight (oz/sq.yd)
Packing	20pcs/box = 5m <sup>2</sup> /box				
Net Weight	24.5kg/box				
Performance	Critical Radiant Flux	(ASTM E648)	Class 2 Average CRF 0.22/cm <sup>2</sup> or higher		
	Smoke Density	(ASTM E662)	Less than 450		
	Flame-retardant	Fire Defense Law in Japan Authorized No.E2150021			
	Antistatic	Less than 1.0kV (JIS L 1021-16, at 23 degrees centigrade, 25%RH)			
	Formaldehyde Radiation	F☆☆☆☆ Interior-fabrics Performance Evaluation Conference Certified No. J15-31019			
Way of Installation	 Quarter Turn    or  Monolithic				
Recommended Adhesive from TOLI	TOLI ECO GA Cement	(required quantity)	for steel or plastic sub-floor	40 to 60 gram/m <sup>2</sup>	
			for mortar and wood sub-floor	60 to 100 gram/m <sup>2</sup>	
Notes on Installation	⚡Due to the polypropylene structure, pile crushing, color shading, and joints may stand out in monolithic installation. ⚡Apply the adhesive on the whole surface of the sub-floor thinly and evenly. After drying, when the adhesive becomes translucent, install the tiles. Be careful not to put the tiles too tightly.				
Others	Please note that the product has the indigenous odor from its materials.				

MADE IN JAPAN



The color numbers marked ◆ can be coordinated with GA-400.

GA5551	GA4019 (page 79) :	—	—
GA5554	GA4003 (page 78) :	GA4004 (page 78) :	GA4034 (page 79)
GA5556	GA4005 (page 78) :	—	—
GA5557	GA4039 (page 79) :	GA4041 (page 79) :	GA4042 (page 79)





# GA-550

category: carpet tile



Carpet  
Tile



▲ GA5556/GA5601 (GA-560 - page 88)



▲ GA5557/GA4039/GA4041/GA4042 (GA-400 - page 79)